


Eccentric Reducer



ASTM A403 / ANSI B16.9

Part Number	Dimensions (mm)									
	Nominal Pipe Size			Sch	O/D (LE)	O/D (SE)	Wall (LE)	Wall (SE)	A	Weight Kg/Pce
080X025ES406	3"	X	1"	40s	88.9	33.4	5.49	3.38	88.9	1.00
080X032ES406	3"	X	1¼"	40s	88.9	42.2	5.49	3.56	88.9	1.00
080X040ES406	3"	X	1½"	40s	88.9	48.3	5.49	3.68	88.9	1.00
080X050ES406	3"	X	2"	40s	88.9	60.3	5.49	3.91	88.9	1.00
080X065ES406	3"	X	2½"	40s	88.9	73.0	5.49	5.16	88.9	1.00
100X040ES406	4"	X	1½"	40s	114.3	48.3	6.02	3.68	101.6	1.60
100X050ES406	4"	X	2"	40s	114.3	60.3	6.02	3.91	101.6	1.60
100X065ES406	4"	X	2½"	40s	114.3	73.0	6.02	5.16	101.6	1.60
100X080ES406	4"	X	3"	40s	114.3	88.9	6.02	5.49	101.6	1.60
125X050ES406	5"	X	2"	40s	141.3	60.3	6.55	3.91	127.0	2.75
125X065ES406	5"	X	2½"	40s	141.3	73.0	6.55	5.16	127.0	2.75
125X080ES406	5"	X	3"	40s	141.3	88.9	6.55	5.49	127.0	2.75
125X100ES406	5"	X	4"	40s	141.3	114.3	6.55	6.02	127.0	2.75
150X050ES406	6"	X	2"	40s	168.3	60.3	7.11	3.91	139.7	3.95
150X065ES406	6"	X	2½"	40s	168.3	73.0	7.11	5.16	139.7	3.95
150X080ES406	6"	X	3"	40s	168.3	88.9	7.11	5.49	139.7	3.95
150X100ES406	6"	X	4"	40s	168.3	114.3	7.11	6.02	139.7	3.95
150X125ES406	6"	X	5"	40s	168.3	141.3	7.11	6.55	139.7	3.95
200X100ES406	8"	X	4"	40s	219.1	114.3	8.18	6.02	152.4	6.50
200X125ES406	8"	X	5"	40s	219.1	141.3	8.18	6.55	152.4	6.50
200X150ES406	8"	X	6"	40s	219.1	168.3	8.18	7.11	152.4	6.50

*Grade 316/L

*Schedule 40s Wall Thickness

*Seamless Construction

*Dimensions are for guidance only – Please call to confirm if critical!